

**Simply child's play.**

**Getting started with the classic sensor.**

Are you toying with the idea of fitting a motion detector to your building? The infrared controlled IS 140-2 motion detector gives you all the benefits of a modern detector. Needless to say, we always use the very latest technology for our bestsellers too. For instance, we have given the product in its current generation even more class: larger adjustment angle, even longer reach and even better detection performance. Treat your home to intelligent sensor technology.



140°, 14 m max.

EAN IS 140-2 white	4007841 608910
EAN IS 140-2 black	4007841 608811
Type	motion detector
Dimensions (HxWxD)	70 x 86 x 95 mm
Power supply	230 - 240 V, 50 Hz
Sensor type	passive infrared
Where to use	indoors and outdoors
Installation	wall
Output	max. 1000W (resistive load), max. 6 fluorescent lamps / LED lamps, C ≤ 132 µF
Angle of coverage	140° with sneak-by guard
Capability of masking out individual segments	yes
Swivelling range	180°
Tilting range	90°
Reach	max. 14 m (temperature-stabilised)
Twilight setting	2 - 2,000 lx
Time setting	8 sec - 35 min
IP rating	IP54
Protection class	II
Accessory included	surface-mounting adapter



**Optional accessories**

EAN EWH 07 white	4007841 631765
EAN EWH 07 black	4007841 631864

For wall or corner mounting



UV-resistant plastic



Optional corner wall mount 07 available

